

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Canceled.)

2. (currently amended) A method for controlling an internal combustion engine, the engine being a multi-cylinder engine with a first group of cylinders coupled to an exhaust aftertreatment device and a second group of cylinders being decoupled from the exhaust aftertreatment device, the method comprising:

operating the first group of cylinders at a first operating condition; and

operating the second group of cylinders at a second operating condition, wherein the first operating condition generates a higher torque than said second operating condition and said second operating condition provides positive torque; and

commanding an injector disposed in an engine exhaust to supply reductant to the exhaust aftertreatment device when a temperature in the exhaust aftertreatment device exceeds a threshold temperature when the first group of cylinders is operating at said first operating condition.

3. (previously amended) The method of claim 2 wherein the reductant is urea and the exhaust aftertreatment device is a lean NO_x catalyst.

4. (previously amended) A method for controlling an internal combustion engine, the engine being a multi-cylinder engine with a first group of cylinders coupled to an exhaust aftertreatment device and a second group of cylinders being decoupled from the exhaust aftertreatment device, the method comprising:

operating the first group of cylinders at a first operating condition;

operating the second group of cylinders at a second operating condition, wherein the first operating condition generates a higher torque than said second operating condition and said second operating condition provides positive torque; and

commanding injectors disposed in engine cylinders of said first group of cylinders to inject fuel during an expansion stroke of the engine when a temperature in the exhaust aftertreatment device exceeds a threshold temperature and the first group of cylinders is operating at said first operating condition wherein said exhaust aftertreatment device is a

lean NOx catalyst and said fuel injected during said expansion stroke is supplied to said lean NOx catalyst.

5. (previously amended) The method of claim 2, wherein said first and second operating conditions are such that the engine delivers substantially said driver demanded torque.

6. (previously amended) The method of claim 2, further comprising:
performing said operating steps when a temperature in the exhaust aftertreatment device is less than a threshold temperature.

7. (previously amended)) A method for controlling an internal combustion engine, the engine being a multi-cylinder engine with a first group of cylinders coupled to an exhaust aftertreatment device and a second group of cylinders being decoupled from the exhaust aftertreatment device, the method comprising:

operating the first group of cylinders at a first operating condition;

operating the second group of cylinders at a second operating condition, wherein the first operating condition generates a higher torque than said second operating condition and said second operating condition provides positive torque wherein the exhaust aftertreatment device is a lean NOx catalyst and said operating steps are performed when a quantity of reductant stored in said lean NOx catalyst is less than a predetermined quantity.

8. (original) The method of claim 7 wherein said stored quantity is based on an amount of reductant stored in said catalyst under predetermined conditions.

9. (original) The method of claim 8 wherein said predetermined conditions include a temperature in the lean NOx catalyst exceeding a threshold temperature.

10. (canceled)

11. (original) A method for controlling torque in an internal combustion engine, the engine being a multi-cylinder engine with a first group of cylinders coupled to a first exhaust aftertreatment device and a second group of cylinders coupled to a second exhaust aftertreatment device, the engine having first and second injectors disposed in an engine exhaust, the injectors being capable of supplying reductant to the first and second aftertreatment devices, respectively, the method comprising:

operating the first group of cylinders at a first operating condition;

operating the second group of cylinders at a second operating condition, wherein said first operating condition generates a higher torque than said second operating condition; and commanding the first injector to provide reductant to the first aftertreatment device when temperature in the first aftertreatment device exceeds a threshold temperature.

12. (previously amended) The method of claim 11 wherein said operating steps are initiated when temperature in the first and second aftertreatment devices is less than said threshold temperature.

13. (previously amended) The method of claim 12 wherein said first operating condition causes the first aftertreatment device to achieve said threshold temperature.

14. (original) The method of claim 12 wherein said threshold temperature is 350 degrees C.

15. (previously amended) The method of claim 11, further comprising: selecting said second operating condition to provide a driver demanded torque by the first and second groups of cylinders.

16. (previously amended) The method of claim 11, further comprising: discontinuing said commanding to the first injector when a desired amount of reductant has been supplied to the first aftertreatment device.

17. (previously amended) The method of claim 16, further comprising:
operating the first group of cylinders at said second operating condition;
operating the second group of cylinders at said first operating condition; and
commanding the second injector to provide reductant to the second aftertreatment device when temperature in the second aftertreatment device exceeds said threshold temperature.

18. (canceled)

19. (currently amended) The method of claim 21, further comprising: at least one additional exhaust manifold coupled to the second group of cylinders, wherein said exhaust manifold conducts exhaust gases from the cylinders to which it is coupled.

20. (previously amended) The method of claim 21 wherein the groups of cylinders comprise at least one cylinder in each group.

21. (previously amended) A system for controlling a multi-cylinder internal combustion engine, the engine having a first group of cylinders and a second group of cylinders wherein the first and second groups of cylinders are mutually exclusive, comprising:

a first exhaust manifold coupled to the first group of cylinders;

an exhaust aftertreatment device coupled to the exhaust manifold;

an electronic control unit coupled to the engine, said electronic control unit operating the first group of cylinders at a first operating condition and operating the second group of cylinders at a second operating condition, wherein said first and second operating conditions provide positive and unequal torques; and

a reductant injector located upstream of said exhaust aftertreatment device, said injector being coupled to said electronic control unit wherein said electronic control unit commands said injector to inject reductant when a temperature in said first aftertreatment device exceeds a threshold temperature.

22-27. (canceled)

28. (currently amended) A system for controlling a multi-cylinder internal combustion engine, the engine having a first group of cylinders and a second group of cylinders wherein the first and second groups of cylinders are mutually exclusive, comprising:

a first exhaust manifold coupled to the first group of cylinders;

an exhaust aftertreatment device coupled to the exhaust manifold; and

an electronic control unit coupled to the engine, said electronic control unit operating the first group of cylinders at a first operating condition and operating the second group of cylinders at a second operating condition, wherein said first and second operating conditions provide positive and unequal torques, said engine is a lean burn gasoline engine, said exhaust aftertreatment device is a lean NOx trap, and said first operating conditions cause temperature in said lean NOx trap to be lower than an upper operating temperature of said lean NOx trap.

29. (previously amended) The system of claim 28 wherein said upper operating temperature is approximately 425 degrees C.

30. (previously amended) A method for controlling a diesel engine, the engine being a multi-cylinder engine having a first group of cylinders coupled to a first lean NOx catalyst and a second

group of cylinders coupled to a second lean NOx catalyst wherein said first and second groups of cylinders are mutually exclusive, the method comprising:

- discontinuing fuel delivery to the first group of cylinders;
- operating the second group of cylinders at an operating condition providing a driver demanded torque with the fuel delivery to the first group of cylinders being discontinued;
- and
- supplying reductant to the first lean NOx catalyst the second group of cylinders being at an operating condition providing a driver demanded torque.

31. (previously amended) The method of claim 30, further comprising:

- discontinuing supplying reductant when the lean NOx catalyst has substantially reached storage capacity; and
- resuming fuel delivery to the first group of cylinders.

32. (canceled)

33. (previously amended) A method for controlling a diesel engine, the engine being a multi-cylinder engine having a first group of cylinders coupled to a lean NOx catalyst, a second group of cylinders not coupled to the lean NOx catalyst, and a reductant injector disposed in an engine exhaust coupled to the first group of cylinders for providing reductant to the lean NOx catalyst, the method comprising:

- operating said first and second groups of cylinders according to a first set of operating conditions when a driver demanded torque is greater than a predetermined torque; and

- operating said first and second group of cylinders according to a second set of operating conditions when said driver demanded torque is less than said predetermined torque wherein said first and second sets of operating conditions are such that a torque provided by said first group of cylinders is different than a torque provided by said second group of cylinders and said first set of operating conditions, further comprises:

- operating the first group of cylinders at a first operating point;

- operating the second group of cylinders at a second operating point, wherein said first operating point generates a higher torque than said second operating point and said second operating point provides positive torque; and

- commanding said injector to provide reductant to the lean NOx catalyst when a temperature within the lean NOx catalyst exceeds a predetermined temperature.

34. (previously amended) A method for controlling a diesel engine, the engine being a multi-cylinder engine having a first group of cylinders coupled to a lean NOx catalyst, a second group of cylinders not coupled to the lean NOx catalyst, and a reductant injector disposed in an engine exhaust coupled to the first group of cylinders for providing reductant to the lean NOx catalyst, the method comprising:

operating said first and second groups of cylinders according to a first set of operating conditions when a driver demanded torque is greater than a predetermined torque; and

operating said first and second group of cylinders according to a second set of operating conditions when said driver demanded torque is less than said predetermined torque wherein said first and second sets of operating conditions are such that a torque provided by said first group of cylinders is different than a torque provided by said second group of cylinders, and said second set of operating conditions further comprises:

discontinuing fuel delivery to the first group of cylinders;

operating the second group of cylinders at an operating point which causes the engine to provide said operator demanded torque with fuel delivery to the first group of cylinders being discontinued; and

commanding said injector to provide reductant to the lean NOx catalyst while operating the second group of cylinders at an operating point which causes the engine to provide said operator demanded torque with fuel delivery to the first group of cylinders being discontinued.

35. (previously amended) The method of claim 33 wherein said predetermined torque is based on at least one of: ambient temperature, engine coolant temperature, engine speed, age of the lean NOx catalyst, output from an exhaust gas composition sensor disposed in the engine exhaust, a throttle valve position, an EGR valve position, and timing of valves disposed in engine cylinders.

36. (canceled)

37. (currently amended) A method for controlling temperature of an internal combustion engine exhaust gas aftertreatment device, such method comprising:

operating a first portion of a plurality of engine cylinders at a first torque output and operating a second portion of said plurality of engine cylinders at a second torque output when temperature in the aftertreatment device is not within a desired temperature range, the overall torque output of the engine is substantially an operator demanded torque, said first portion of cylinders is coupled to the aftertreatment device, said operator demanded torque is based on a

position of an accelerator pedal. The method of claim 40 wherein and said second portion of engine cylinders is decoupled from the aftertreatment device.

38. (currently amended) The method of claim 3740 wherein said temperature is based on an output from a temperature sensor located proximate to said aftertreatment device.

39. (currently amended) The method of claim 3740 wherein said temperature is based on a model of aftertreatment.

40. (canceled)

41. (currently amended) The method of claim 3740 wherein said exhaust aftertreatment device is a particulate filter, the desired temperature range comprises a temperature greater than an ignition temperature of particulate matter collected in said particulate filter, and said first torque output is greater than a second torque output.

42. (currently amended) The method of claim 3740 wherein said exhaust aftertreatment device is a lean NOx catalyst, the desired temperature range is greater than an activation temperature of said lean NOx catalyst, and said first torque output is greater than a second torque output.

43. (currently amended) The method of claim 3740 wherein said exhaust aftertreatment device is a lean NOx trap, the desired temperature range for purging NOx from said lean NOx trap is between 250 and 425 degrees C, the first torque output is greater than the second torque output when the temperature is less than 250 degrees C and the first torque output is less than the second torque output when the temperature is greater than 425 degrees C.

44. (currently amended) The method of claim 3740 wherein said exhaust aftertreatment device is a lean NOx trap, the desired temperature range for causing SOx to desorb from said lean NOx catalyst is a temperature greater than 650 degrees C, the first torque output is greater than the second torque output.